

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

2

EUROPEAN PATENT APPLICATION

21 Application number: 88105558.6

51 Int. Cl.4: H02N 13/00

22 Date of filing: 07.04.88

30 Priority: 14.04.87 JP 89848/87

43 Date of publication of application:
14.12.88 Bulletin 88/50

84 Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE

71 Applicant: **KABUSHIKI KAISHA ABISARE**
Kaneshiro 66
Kakegawa-shi Shizuoka-ken(JP)


72 Inventor: **Kasahara, Keiji**
Kakegawa 1128-14
Kakegawa-shi Shizuoka-ken(JP)

74 Representative: **Klingseisen, Franz, Dipl.-Ing.**
et al
Dr. F. Zumstein Dipl.-Ing. F. Klingseisen
Bräuhäusstrasse 4
D-8000 München 2(DE)

54 **Electrostatic holding apparatus.**

57 An electrostatic holding apparatus having, in sequentially laminated relation, an insulating base layer, a set of electrodes to which positive and negative charges are respectively applied, and an adsorbing layer which is induced by the set of electrodes for attracting and holding an object thereagainst by an electrostatic attracting force. A power supply circuit is connected to the set of electrodes for respectively applying positive and negative charges to the first and second electrodes of the set. The power supply circuit includes a DC power source, and also includes a switching arrangement for permitting reversing of the charges as applied to the electrodes so that reverse charges are applied to the electrodes each time a prior object is peeled off the adsorbing layer and a new object is attached thereto.

FIG. 1



ELECTROSTATIC HOLDING APPARATUS

FIELD OF THE INVENTION

The present invention relates to an electrostatic holding apparatus having, a sequentially laminated relationship, an insulating base layer, a set of electrodes to which positive and negative charges are respectively applied, and an adsorbing layer which is induced by the set of electrodes for holding an object by an electrostatic attracting force, whereby the object to be adsorbed can be stably held by a large attracting force.

BACKGROUND OF THE INVENTION

In a known electrostatic holding apparatus for attracting and holding an object to be adsorbed by use of the Coulomb force of static electricity, an insulating base layer, a set of electrodes, and an adsorbing layer are sequentially laminated. In such apparatus, positive and negative charges are respectively applied to the set of electrodes by conduction, and the adsorbing layer is induced, whereby an object to be adsorbed is adsorbed and held by the electrostatic attracting force of the adsorbing layer. Such electrostatic holding apparatus is disclosed in JP-B 55-20830 and JP-B 57-58872.

However, such conventional electrostatic holding apparatuses have a disadvantage in that, when the adsorbed object is peeled off or removed from the apparatus, the attracting force is weakened. Thus, when a further object is to be attached to the apparatus, there is a problem in that a sufficient attracting force may not be effected, and the object to be adsorbed may not be stably held.

It is, therefore, an object of the present invention to provide an improved electrostatic holding apparatus of this general type, which apparatus overcomes the above disadvantage.

To accomplish this object, according to the invention, there is provided an electrostatic holding apparatus having, sequentially laminated, an insulating base layer, a set of electrodes to which positive and negative charges are respectively applied by conduction, and an adsorbing layer which is induced by the set of electrodes and adsorbs and holds an object to be adsorbed by an electrostatic attracting force. This apparatus is characterized by providing a power supply circuit for respectively applying the opposite (i.e., reversing the) positive and negative charges to the set of electrodes after the object adsorbed and held to the adsorbing layer is peeled off so that a new object can be adsorbed and held by the apparatus.

According to the invention, after completion of the non-conduction state (that is, after removal of the object), the opposite positive and negative charges are respectively applied to the set of electrodes by the power supply circuit. Therefore, by setting the apparatus into the non-conducting state, the object held on the apparatus can be easily peeled off. On the other hand, by applying the opposite positive and negative charges after completion of the non-conduction state, a new object to be adsorbed is adsorbed and held by a large attracting force.

BRIEF DESCRIPTION OF THE DRAWINGS

An embodiment of the present invention will now be described in detail in conjunction with the accompanying drawings wherein:

Fig. 1 is an exploded perspective view of the invention;

Fig. 2 is a plan view thereof;

Fig. 3 is a cross-sectional view thereof;

Fig. 4 is a cross-sectional view of a state in which an object to be adsorbed is peeled off; and

Fig. 5 is a cross-sectional view of a state in which a new object to be adsorbed is adsorbed.

DETAILED DESCRIPTION

Figs. 1 to 4 show an embodiment of the invention. In Figs. 1 and 2, an electrostatic holding apparatus 2 is constituted by sequentially laminating an insulating base layer 4, a set of electrodes 6 and 8 arranged like a comb to which positive and negative charges are respectively applied by conduction, and an adsorbing layer 12 which is induced by the set of electrodes 6 and 8 and adsorbs and holds an object 10 to be adsorbed by the electrostatic attracting force.

As shown in Fig. 3, the electrostatic holding apparatus 2 has a DC power source 16 connected to the set of electrodes 6 and 8, thereby applying positive and negative charges, respectively. Since the adsorbing layer 12 is induced by the set of electrodes 6 and 8, when the object 10 comes into contact with layer 12, the charges of the polarity different from the charges of each of the electrodes 6 and 8 are generated by electrostatic induction in the portions of the object 10 which face the electrodes 6 and 8. Thus, an electrostatic attracting force acts between the charges caused in the object 10 and the charges of each of the electrodes 6 and 8, thereby adsorbing (i.e., attracting) and hold-

ing the object 10 to the surface of the adsorbing layer 12.

As described above, the electrostatic holding apparatus for adsorbing and holding the object 10 has an inconvenience in that, when one object 10 to be adsorbed is peeled off, the attracting force is weakened. Thus, there is a problem such that a sufficient attracting force may not be effected so that a further object 10 may not be stably held.

In this invention, there is provided a power supply circuit 14 for applying the opposite positive and negative charges to the set of electrodes 6 and 8 after completion of the non-conduction state when the first object 10 adsorbed and held to the adsorbing layer 12 is peeled off, and before a new object 10 is adsorbed and held. The power supply circuit 14 comprises: the power supply section 16 to supply a DC power source; and a change-over switch 18 for switching or reversing the DC power source of the power supply section 16 in order to apply the opposite positive and negative charges to the set of electrodes 6 and 8 after completion of the non-conduction state. Switch 18 can be manually actuated.

The material of the layer 12 is, for example, polyester or P.C. (polycarbonate) or A.B.S. (acrylonitrile butadiene styrene), or materials of similar properties. Object 10, on the other hand, typically comprises a thin sheetlike member such as a paper sheet, a film (as for an overhead projector), or the like.

The operation will now be explained.

The DC power source of the power supply section 16 is switched by the switch 18 and supplied to the set of electrodes 6 and 8. For example, as shown in Fig. 3, when the positive charges are applied to the electrode 6 and the negative charges are applied to the other electrode 8, the adsorbing layer 12 is induced. When a first object 10 comes into contact with the adsorbing layer 12, the charges of polarity different from that of the charges of the electrodes 6 and 8 are caused by electrostatic induction in the portions of the object 10 which face the electrodes 6 and 8. Thus, the electrostatic attracting force acts between the charges generated in the object 10 and the charges of the electrodes 6 and 8, thereby adsorbing and holding the object 10 to the surface of the adsorbing layer 12.

As shown in Fig. 4, when this first object 10 as adsorbed and held to the adsorbing layer 12 is peeled off, the attracting force of the adsorbing layer 12 is slightly weakened. Therefore, when the first object 10 as adsorbed and held to the adsorbing layer 12 is peeled off, and a new object 10 is to be adsorbed and held, the DC power source of the power supply section 16 is switched by the change-over switch 18 so as to apply the opposite

positive and negative charges to the set of electrodes 6 and 8 respectively, after completion of the non-conduction state.

In this manner, by setting the electrodes 6 and 8 into the non-conduction state, as by disrupting the supply of DC electrical power (such as moving switch 18 into an open position), the object 10 adsorbed and held to the adsorbing layer 12 can be easily peeled off. On the other hand, for example, as shown in Fig. 5, after the non-conduction state, the negative charges are applied to the electrode 6 and the positive charges are applied to the other electrode 8. Therefore, when the next object 10 comes into contact with the adsorbing layer 12, the charges of polarity different from that of the charges of each of the electrodes 6 and 8 are caused by electrostatic induction in the portions of the object 10 which face the electrodes 6 and 8. Thus, the electrostatic attracting force acts between the charges caused in the object 10 and the charges of the electrodes 6 and 8, thereby enabling the next object 10 to be adsorbed and held to the surface of the adsorbing layer 12 by a sufficient attracting force.

Thus, the object to be adsorbed can be stably held by the large attracting force.

As described above, according to the invention, the opposite positive and negative charges are respectively applied to the set of electrodes by the power supply circuit after completion of the non-conduction state. Thus, a first object can be easily peeled off by setting the set of electrodes into the non-conduction state. On the other hand, by applying the opposite positive and negative charges to the set of electrodes after completion of the non-conduction state, a new object to be adsorbed can be adsorbed and held by a large attracting force.

Due to this, it is possible to realize an electrostatic holding apparatus which can stably hold an object to be adsorbed by a large attracting force.

Claims

1. In an electrostatic holding apparatus having, in sequentially laminated relation, an insulating base layer, a set of electrodes to which positive and negative charges are respectively applied by conduction, and an adsorbing layer which is induced by said set of electrodes and adsorbs and holds an object to be adsorbed by an electrostatic attracting force, the improvement comprising power supply circuit means connected to said set of electrodes for respectively applying opposite positive and negative charges to said set of electrodes after completion of a non-conduction state when a first

said object as adsorbed and held to said adsorbing layer is peeled off and a second said object is adsorbed and held to said adsorbing layer.

2. An apparatus according to Claim 1, wherein said power supply circuit means includes a DC power source having first and second terminals, and electrically conductive means connected between said first and second terminals and said set of electrodes, said conductive means including switching means for selectively permitting said first and second terminals to be alternately and oppositely connected to first and second electrodes of said set for alternately reversing the electrical polarity of the electrodes.

5

10

15

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4





FIG. 5



EUROPEAN PATENT APPLICATION

Application number: **88105558.6**

Int. Cl. 4: **H02N 13/00**

Date of filing: **07.04.88**

Priority: **14.04.87 JP 89848/87**

Date of publication of application:
14.12.88 Bulletin 88/50

Designated Contracting States:
AT BE CH DE ES FR GB GR IT LI LU NL SE

Date of deferred publication of the search report:
26.04.89 Bulletin 89/17

Applicant: **KABUSHIKI KAISHA ABISARE**
Kaneshiro 66
Kakegawa-shi Shizuoka-ken(JP)


Inventor: **Kasahara, Keiji**
Kakegawa 1128-14
Kakegawa-shi Shizuoka-ken(JP)

Representative: **Klingseisen, Franz, Dipl.-Ing.**
et al
Dr. F. Zumstein Dipl.-Ing. F. Klingseisen
Bräuhäusstrasse 4
D-8000 München 2(DE)

Electrostatic holding apparatus.

An electrostatic holding apparatus (2) having, in sequentially laminated relation, an insulating base layer (4), a set of electrodes (6,8) to which positive and negative charges are respectively applied, and an adsorbing layer (12) which is induced by the set of electrodes (6,8) for attracting and holding an object (10) thereagainst by an electrostatic attracting force. A power supply circuit (14) is connected to the set of electrodes (6,8) for respectively applying positive and negative charges to the first and second electrodes (6,8) of the set. The power supply circuit (14) includes a DC power source (16), and also includes a switching arrangement (18) for permitting reversing of the charges as applied to the electrodes (6,8) so that reverse charges are applied to the electrodes (6,8) each time a prior object (10) is peeled off the adsorbing layer (12) and a new object (10) is attached thereto.

FIG. 1





EP 88 10 5558

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 4)
A	GB-A-1 352 715 (STEVKO) * Whole document * ---	1	H 02 N 13/00
A	US-A-4 016 456 (BIRKS et al.) * Whole document * -----	1	
			TECHNICAL FIELDS SEARCHED (Int. Cl. 4)
			H 02 N 13/00 H 01 L 21/00
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 07-02-1989	Examiner LE GUAY P.A.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			